

Catalys® THF

DESCRIPTION

Catalys THF is high quality, multifunctional fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir. It is compatible with many tractor-hydraulic fluids available on the market.

APPLICATION / BENEFITS

Catalys THF meets the requirements of major tractor manufacturers performance specification such as JOHN DEERE J20C; FORD/NEW HOLLAND M2C134-D, FNHA-2-C-201; MASSEY FERGUSON M1135, M1141, M1143 and M1145; CASE MS1206, MS1210; WHITE FARM Q-1826; KUBOTA UDT; CATERPILLAR TO-2; VOLVO WB 101; VICKERS I-286-S and M-2950-S; AGCO-ALLIS Power Fluid 821XL; INTERNATIONAL HARVESTER B-5 et B-6 and CASE NEW HOLLAND (CNH) MAT-3505, 3506, 3509 et 3525. It is best practice to always confirm specification required in the equipment owner's manual prior to use multifunctional tractor hydraulic fluids.

This oil has been developed with carefully selected additives to provide the following features and benefits:

- Prevents grabbing or chattering of wet brakes and PTO clutches
- Oxidation protection – controls sludge and deposits; minimizes viscosity increase
- Reduces component wear and improves equipment life
- Prevents oil foaming tendency
- Compatible with commonly used seals, gaskets, and packing materials

PHYSICAL PROPERTIES	ASTM METHOD	Super Trans TDH
Color		Amber
Kinematic Viscosity at 40°C, cSt	D445	61,0
Kinematic Viscosity at 100°C, cSt	D445	9,3
Viscosity Index, min.	D2270	132
Dynamic viscosity, Brookfield, cP @ -35C	D2983	48000 typ.
Density at 15°C, kg/L	D1298	0,865
Flash Point, °C	D92	210
Pour Point, °C	D97	-39

The values listed above are typical of current production, variations in these properties may occur.

AVAILABLE PACK SIZES

	Bulk	Drum	Pail
Catalys THF	07-1893-00	07-1893-05	07-1893-10

THE PACK SIZES ABOVE ARE OUR STANDARD PACK SIZES. PLEASE COMMUNICATE WITH US TO FIND OUT FORMATS AVAILABLE LOCALLY.

HEALTH / SAFETY

GHS compliant English and French Safety Data Sheets are available at catalyslubricants.ca under 'Safety Data Sheets'. Keep container closed when not in use. Please refer to the SDS for safe handling information. Always take used grease and containers to an authorized collection point. Avoid discharge into the environment. As with any grease, keep out of reach of children and animals.

QUALITY

Catalys Lubricants partners with respected industry suppliers to bring you high quality products. For more information, contact your local Catalys Representative. Please ensure this product is right for the equipment by following the recommendations of the equipment operating manual.

CONTACT US

British Columbia	Alberta	Manitoba	Ontario	Quebec
7483 Progress Way	Unit 130, 16815 117 th Ave NW	25 Midland Street	3462 White Oak Road	2320, rue de la Métropole

Delta, BC	Edmonton, AB	Winnipeg, MB	London, ON	Longueuil, QC
V4G 1E7	T5M 3V6	R3E 3J6	N6E 2Z9	J4G 1E6
855.946.4226	877.222.8507	855.755.6737	800.673.6231	800.363.0590

Catalys® is a registered trademark of Entreprises Émile Crevier Inc.