

## Multi Pro HiTemp Grease

### DESCRIPTION

Catalys Multi Pro HiTemp Grease NLGI 2 is a multi-purpose, EP, premium grease, especially suited for heavy-duty application and manufactured from high quality base oil and additives. Catalys Multi Pro protects equipment and parts against wear, rust, and corrosion. This grease provides excellent adherence to metal surfaces and resistance to water washout. Catalys Multi Pro HiTemp Grease NLGI 2 is designed to meet the GC/LB specification for use in on highway Chassis and Bearing applications.

**Application:** Heavy-Duty Industrial and automotive service, multi-purpose, marine. Heavy Duty On Highway applications including Chassis and Bearings requiring GB/LB specifications.

PROPERTIES	Tests	
NLGI Grade		2
Colour and appearance	Visual	Red, tacky
Worked Penetration, 60 strokes, 25°C	ASTM D217	265-295
Dropping Point, °C	ASTM D2265	260
Mineral Base Oil Viscosity, cSt at 40°C	ASTM D445	220
Timken OK Load, kg (Lb)	ASTM D2509	22.7 (50)
4 Ball EP, wear scar diameter, mm	ASTM D2266	0.43
4 Ball EP, Weld Load, kg	ASTM D2596	315 min.
Operating Temperature Range, °C		-15 to 210

### Available Package Size

Multi Pro HiTemp Grease

**170 Kg   55 Kg   15.9 Kg**  
07-0922-01, 07-0922-54, 07-0922-15