



# **OptiSorb**®

# **Premium Spill Control Solid**

## **Description**

OptiSorb® Premium Oil Absorbent is an all-purpose economical floor sweep product used to manage and contain occasional spills of water, oil and grease. OptiSorb® is a granular, natural diatomaceous earth based product that can absorb its own weight in liquid.

OptiSorb® is ideal for road side spills, service stations, maintenance workshops, parking areas, refuelling areas, paint and panel shops and automotive workshops. OptiSorb® leaves surfaces dryer and less slippery.

#### **Advantages**

- Non-hazardous
- Economical spill control solid
- Low bulk density and high absorptive capacity

# **Application**

- For use on hard surfaces wherever oils, fuels, chemicals and liquids are stored, handled and spilt
- Placed around spills for containment
- Placed on top of fluids to absorb the liquid and begins to clump or solidify for easy pick upup and recovered for disposal.

#### **Use and Storage**

Efforts should be made to minimize or eliminate spills. Optisorb has a long shelf life provided it is kept under ideal storage conditions. Keep packages closed while not in use, store in a cool, dry area.

## **Health, Safety, & Environment**

GHS compliant Safety Data Sheets are available at nemco.ca under the Safety Data Sheets. For SDS in French, please contact info@nemco.ca. This material is not hazardous. The SDS contains valuable information critical to the safe handling and proper use of the product. Avoid discharge into drains, soil, or water. As with any industrial product, keep out of reach of children and animals.

#### Quality

Nemco works with respected industry suppliers. Optisorb is a registered trademark of EP Minerals. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your local sales representative.

# **Typical Characteristics - Optisorb®**

Properties	Performance	Properties	Performance
Loose Bulk Density	22 - 24lb / cu. Ft.	рН	6.5
Moisture Content	0.2 - 0.8%	Water Absorption	110%
Hardness, ASTM E-728	>90%	Oil Absorption	100%

These characteristics are typical of current production, variations in these characteristics may occur.

#### **Availability and product codes**

Pack size	25lb bag	Pallet	
Optisorb®	CHCPZ0014	80 x 25lb bags, 1,265kg	
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca		

OptiSorb® Issue Date: 12/09/15 Revision Date: 08/11/21 Rev#: 1 Page 1 of 1