

## 1. Identification

<b>Product identifier</b>	<b>HVI ISO VG 22</b>		
<b>Other means of identification</b>	NM0266-031721		
<b>Recommended use</b>	Industrial lubricant for hydraulics		
<b>Recommended restrictions</b>	Not for food, drug, or household use.		
<b>Manufacturer/Importer/Supplier/Distributor information</b>			
<b>Manufacturer</b>			
<b>Company name</b>	Nemco Resources Ltd		
<b>Address</b>	25 Midland Street Winnipeg, MB R3E 3J6 Canada		
<b>Telephone</b>	Phone:	204-788-1030	
	Fax:	204-788-1593	
	Toll Free:	855-755-6737 (M-F 8am-4:30pm)	
<b>Website</b>	www.nemco.ca/msds-safety-information		
<b>E-mail</b>	info@nemco.ca		
<b>Emergency phone number</b>	NEMCO:	855-755-6737 (M-F 8am-4:30pm)	
<b>Supplier</b>	See above.		

## 2. Hazard identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Sensitization, skin	Category 1
<b>Environmental hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Warning	
<b>Hazard statement</b>	May cause an allergic skin reaction.	
<b>Precautionary statement</b>		
<b>Prevention</b>	Avoid breathing mist or vapour. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.	
<b>Response</b>	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.	
<b>Storage</b>	Store away from incompatible materials.	
<b>Disposal</b>	Dispose of container in accordance with local, regional, national and international regulations.	
<b>Other hazards</b>	None known.	
<b>Supplemental information</b>	None.	

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
2,6-Di-tert-butylphenol		128-39-2	1-5*
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	0.1-1*
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	60-80*
Distillates (petroleum), hydrotreated light paraffinic		64742-55-8	0.1-1*
Distillates (petroleum), solvent-dewaxed heavy paraffin		64742-65-0	0.1-1*

Chemical name	Common name and synonyms	CAS number	%
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		72623-86-0	10-30*
Petroleum distillates, solvent dewaxed light paraffinic		64742-56-9	0.1-1*
Triphenyl phosphite		101-02-0	0.1-1*
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)-		4259-15-8	1-5*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** \*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
<b>Ingestion</b>	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Sensitisation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon. Oxides of phosphorus.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Prevent entry into waterways, sewer, basements or confined areas.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
<b>Environmental precautions</b>	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

## 8. Exposure controls/Personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	1 mg/m <sup>3</sup>	Mist.

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	1 mg/m3	Mist.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	1 mg/m3	Mist.

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value	Form
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

Components	Type	Value
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	15 minute	10 mg/m3
	8 hour	5 mg/m3

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields.

**Skin protection****Hand protection**

Impervious gloves. Confirm with reputable supplier first.

**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

**9. Physical and chemical properties**

<b>Appearance</b>	Liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Amber
<b>Odour</b>	Mild hydrocarbon

<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	> 110.0 °C (> 230.0 °F) TCC
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not applicable
<b>Flammability limit - upper (%)</b>	Not applicable
<b>Explosive limit - lower (%)</b>	Not applicable
<b>Explosive limit - upper (%)</b>	Not applicable
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0.85
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	24 cSt @ 40°C
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

---

## 10. Stability and reactivity

---

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidising agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon. Oxides of phosphorus.

---

## 11. Toxicological information

---

### Information on likely routes of exposure

<b>Inhalation</b>	Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).
<b>Skin contact</b>	Contains a potential skin sensitizer.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	May cause stomach distress, nausea or vomiting.

**Symptoms related to the physical, chemical and toxicological characteristics**      Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
2,6-Di-tert-butylphenol (CAS 128-39-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 10000 mg/kg
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Mouse	2995 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.5 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	2.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	5000 mg/kg, ECHA
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	> 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Triphenyl phosphite (CAS 101-02-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 6.7 mg/l/4h, 1 Hours, ECHA
<i>Oral</i>		
LD50	Rat	1590 mg/kg, ECHA
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)- (CAS 4259-15-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	5000 mg/kg
<i>Oral</i>		
LD50	Rat	3100 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitisation</b>		
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.	
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Contains < 3% (w/w) DMSO-extract	
<b>ACGIH Carcinogens</b>		
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A2 Suspected human carcinogen.	
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	A2 Suspected human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Suspected human carcinogen.	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Suspected human carcinogen.	
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Suspected human carcinogen.	
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)	Suspected human carcinogen.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.	
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	



<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.
<b>Further information</b>	Not available.

## 12. Ecological information

**Ecotoxicity** See below

### Ecotoxicological data

Components	Species	Test Results
2,6-Di-tert-butylphenol (CAS 128-39-2)		
Crustacea	EC50 Daphnia	0.45 mg/L, 48 Hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (CAS 72623-86-0)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Petroleum distillates, solvent dewaxed light paraffinic (CAS 64742-56-9)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)- (CAS 4259-15-8)		
Crustacea	EC50 Daphnia	1.25 mg/L, 48 Hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### Bioaccumulative potential

**Mobility in soil** No data available.

**Mobility in general** Not available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

**General** Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

### Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

## 15. Regulatory information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada CEPA Schedule I: Listed substance**

Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, Listed.  
(T-4)- (CAS 4259-15-8)

**Canada Priority Substances List (Second List): Listed substance**

Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, Listed.  
(T-4)- (CAS 4259-15-8)

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**WHMIS status** Hazardous

**International regulations**

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	/ 1
<b>FLAMMABILITY</b>	0
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X



**Issue date** 06-July-2021

**Revision date** 06-July-2021

**Version No.** 01

**Other information** For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

**Disclaimer** The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Prepared by** Dell Tech Laboratories Ltd. Phone: (519) 858-5021