

Kerosene Low Sulphur

Description

Nemco Kerosene is a low odour, low sulphur fuel for use as a heating fuel or for illumination. Ensure adequate and appropriate ventilation and exhaust systems are in place when using this product, and ensure emissions comply with local environmental protection legislation.

Applications

- Oil burning appliances and kerosene heaters
- Most atomizing-type burner applications including medium capacity commercial and industrial burners

Use and Storage

Always read and follow your equipment manual. Kerosene has a shelf life of 5 years under ideal storage conditions. Keep packages closed while not in use, store in a cool, dry area and away from open heat sources, sparking tools and equipment.

Health, Safety, & Environment

GHS compliant Safety Data Sheets are available at nemco.ca under the Safety Data Sheets. For SDS in French, please contact info@nemco.ca. This material is WHMIS and TDG classified. The SDS contains valuable information critical to the safe handling and proper use of the product. Avoid discharge into drains, soil, or water. As with any chemical, keep out of reach of children and animals.

Quality

Nemco works with respected industry suppliers. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your local sales representative.

Typical Characteristics - Kerosene

Properties	Method	Performance	Properties	Method	Performance
Colour	Appearance	Colourless	Kinematic Vis@40°C mm ² /s	ASTM D445	1.2 - 3.6
SPG, 15.6°C	Internal	0.823	Sulfur, total, % by mass	ASTM D2622	<0.30
Freeze point, °C(°F)	ASTM D2386	-47(-53)	Copper corrosion, 2hr@100°C	ASTM D130	1
Flash point, °C(°F)	ASTM D56	43(109)	Copper corrosion, 3hr@50°C	ASTM D130	1

These characteristics are typical of current production, variations in these characteristics may occur.

Availability and product codes

Pack size	20L pail	205L drum
Kerosene	CHCPZ0044	Special Order
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca	