

# PRODUCT DATA SHEET

# **RV & Marine Standard Winterizer** Recreational Vehicle and Plumbing Antifreeze

# Description

**Nemco RV & Marine Standard Winterizer** is a lowtoxicity recreational vehicle and plumbing antifreeze. This product is suitable for winterizing all potable (drinking) water and/or plumbing systems containing plastic pipes. It is formulated to be used full strength to winterize boats, recreational vehicles, trailers, vacation homes, swimming pools, and a variety of other winter storage applications.

Nemco RV & Marine Standard Winterizer is ready-touse; for maximum freeze and burst protection do not dilute. Drain all water from the system before adding Winterizer and ensure the product has worked its way through the system for adequate protection.

**Typical Characteristics - RV & Marine Standard Winterizer** 

#### **Advantages**

- Ready-to-Use, do NOT dilute
- Low toxicity formula
- Suitable for plastic pipes
- Burst protection down to -50°C

# **Applications**

- Recreational vehicles
- Boats
- Trailers
- Cabin/cottage

# Use and Storage

Always read and follow your equipment manufacturer's winterizing instructions. This product has a typical shelf life of 2 to 3 years under ideal storage conditions. Keep packages closed while not in use, store in a cool, dry area and away from open heat sources, sparking tools and equipment. Keep drum and tote bungs securely in place; as bungs breath, moisture can seep in over time reducing the product's effectiveness. Keep packages closed while not in use, store in a cool and dry area.

## Health, Safety, & Environment

GHS compliant Safety Data Sheets are available at **nemco.ca** under the Safety Data Sheets. For SDS in French, please contact **info@nemco.ca**. This material is WHMIS 2015 and TDG classified. The SDS contains valuable information critical to the safe handling and proper use of the product. Always take used chemical to an authorized collection point. Avoid discharge into drains, soil, or water. As with any chemical, keep out of reach of children and animals.

## Quality

Nemco works with respected industry suppliers. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your local sales representative.

Properties	Method	Performance	Properties Method F		Performance	
Colour	Appearance	Pink	Freeze point, °C(°F)	ASTM D3321	n/a	
SPG, 20°C	Internal	0.980	Burst point, °C(°F)	Industry	-50(-58)	
рН	Internal	7.5 - 8.5	Flash point, °C(°F)	ASTM D56	35(95)	

These characteristics are typical of current production, variations in these characteristics may occur.

# **Availability and product codes**

Pack size		4x3.78L case	20L pail		205L drum			
RV Standard		AIAFZ0090	AIAFZ0091		AIAFZ0092			
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca							
RV Standard	lssu		e Date: 12/09/15 Revision Da		ate: 07/28/21	Rev#: 1	Page 1 o	
NEMCO	25 Midland Stree	et Winnipeg, Manitoba	a Canada	R3E 3J6	TF 1-855-	755-6737	nemco	